

Miniveyor Air VAF-FFD

Fast Floor Dryer System

**Why do we call it a Fast Floor Dryer system?
...because it dries a floor fast, it's that simple!**




Using downdraft technology, the NEW Miniveyor Air VAF-FFD downdraft floor dryer is capable of drying an entire room in minutes. The powerful 6 blade precision fan blade draws down warmer, drier air from the top of the room and blows it across the entire floor. The powerful vane axial fan, driven by a 1/4HP 2-Speed motor, allows 360° directed airflow, and one FFD blower can dry a typical office or room in as little as 15 minutes.



The heavy duty swivel castors provide easy mobility and position the unit at optimum downdraft height. You can stack the dryers for easy storage and transport and the in-built telescopic handled trolley allows you to move the fan from job to job with ease.

Miniveyor Air VAF-FFD The Professional Choice for Floor Drying

- The dual wall tough plastic moulded body will not dent or ding.
- Industry leading 10 year warranty upgrade available on the body.
- Stackable up to 4 high for easy storage and transport.
- 360 degrees directed airflow - no more drying a room one section at a time.
- Multi position versatility.
- In built trolley for easy mobility.
- One dryer can dry a typical room in 15 minutes.
- Built in cord wrap.



**For further Information - Call our Worldwide Sales Line
+44 845 094 2140 or email sales@miniveyor.com
or visit our website www.miniveyor.com**



FOR WORLDWIDE SALES **+44 (0)845 094 2140**
US TOLL FREE **1-866-558-7256**
OR EMAIL sales@miniveyor.com

Miniveyor Products Ltd
Unit 4B Tetbury Ind. Estate
Cirencester Road
Tetbury, Glos,
GL8 8EZ, United Kingdom
Tel: +44 (0)845 094 2140
Fax: +44 (0) 845 496 6018
US Toll Free: 1-866-558-7256
Email: sales@miniveyor.com
Web: www.miniveyor.com



Miniveyor Air VAF-FFD

Specifications



Specifications	VAF-FFD
Max.Air Flow m ³ /hr (CFM)	110V - 5950 (3500) 230V - 5100 (3000)
Motor Specifications	
Voltage	110V 60 Hz or 230V 50 Hz
Phase	Single
Power	¼HP (186W)
Current (Amps)	110V 2.2A / 230V 1.8A
RPM	110V -1476 / 230V -1450
Dimensions	
Length	58cm (23in)
Width	59cm(23¼in)
Height	68cm (26¾in)
Weight	24Kg (53lbs)

The VAF-FFD is supplied complete with Integral Telescopic Handle and Castor Wheel Kit as Standard and is available in 230V & 110V. Custom colours are also available, subject to a minimum order quantity.

The Miniveyor Air VAF-FFD system provides flexibility, versatility and durability and is perfect for use in many different environments including -

- Hotels and Resorts
- Casinos
- Schools, Colleges & Universities
- Restaurants
- Hospitals
- Commercial Office Building & Conference Centres
- Retail Stores & Shopping Malls
- Industrial Facilities
- Restoration & Commercial Cleaning Contractors
- Equipment Rental Outlets

Miniveyor Air

Dual wall construction for rugged reliability.
Resistant to dents, & dings, providing reliable continuous operation and less downtime. Polythene body is corrosion free and not effected by chips or scratches.
Portable and lightweight
11 to 25 kg

V's

Metal Fans

Single layer construction - makes fan more vulnerable to damage, which can then impede fan blade rotation.
Can rust and corrode easily.
Heavier - from 10 kg to 90 kg

NEW VAF Models now come with a Industry Leading 10 Year warranty upgrade on the fan body.

**For further Information - Call our Worldwide Sales Line
+44 845 094 2140 or email sales@miniveyor.com
or visit our website www.miniveyor.com**



FOR WORLDWIDE SALES **+44 (0)845 094 2140**
US TOLL FREE **1-866-558-7256**
OR EMAIL sales@miniveyor.com

Miniveyor Products Ltd
Unit 4B Tetbury Ind. Estate
Cirencester Road
Tetbury, Glos,
GL8 8EZ, United Kingdom
Tel: +44 (0)845 094 2140
Fax: +44 (0) 845 496 6018
US Toll Free: 1-866-558-7256
Email: sales@miniveyor.com
Web: www.miniveyor.com

